

**■ UltraDrive MX2 Series**  
SATA-II, mini-USB connections

**SATA Solid State Drive**



The new UltraDrive MX2 represents a premium consumer offering and fits nicely between our Value Line and Enterprise SSD offerings. The UltraDrive MX2 features the JMicron 616 which enables this SSD to reach an impressive 250MB/s Read and 180MB/s Write speeds. The UltraDrive MX2 also supports the latest GC and Trim features designed to keep this SSD running at optimum performance for the life of the drive.

The UltraDrive MX2 features a new dual-interface for both SATA II and mini-USB connections. The new dual-interface enables this SSD to offer a new level of flexibility and consumer convenience by enabling the customer to use this drive as either an internal SSD or an external SSD.

**Physical Specifications**

Form Factor	2.5" HDD
Capacity*	60GB - 480GB
Dimension	100.2 x 69.9 x 9.5 mm
Interface	SATA II, mini-USB connections
NAND Flash	MLC / SLC
Cache	64MB DRAM Cache
Power Supply	5V ± 10%
Package	Metal housing

**Environmental Specifications**

Operating Shock	1500G
Operating Vibration	16G
Operating Temperature	0°C to +70°C
Operating Humidity	5 to 90%

**Reliability Specifications**

MTBF	1,000,000 hours
Data Reliability	BCH 16/24 bits ECC
Wear Leveling Algor.	Patent Pending

**Performance Specifications**

Part Number	Seq. Read (MB/sec max)	Seq. Write (MB/sec max)
FTD06M225H	240	180
FTD12M225H	240	180
FTD24M225H	240	180
FTM06M225H	240	80
FTM12M225H	240	150
FTM24M225H	240	180
FTM48M225H	240	180

**Ordering Information**

Capacity	MLC	SLC
60GB	FTM06M225H	FTD06M225H
120GB	FTM12M225H	FTD12M225H
240GB	FTM24M225H	FTD24M225H
480GB	FTM48M225H	

© 2011 Super Talent Technology. Specifications subject to change without notice. US patent # 6,547,130 and others apply. 1GB=1,000,000,000 Bytes. Usable capacity may be less than specified after formatting. Actual performance varies depending upon the system configuration and the application used. Performance is highly dependent upon test environment and use case. Consult our benchmarking data for more detailed performance information or benchmark performance in your environment.

■ ■ **UltraDrive MX2 Series**

**SATA Solid State Drive**

**SATA Flash Drive Pin Assignment**

**Power Segment**

PIN	Signal Name	Description
P1	Not Used (3.3V)	N/A
P2	Not Used (3.3V)	N/A
P3	Not Used (3.3V Precharge)	
P4	GND	1 <sup>st</sup> mate
P5	GND	2 <sup>nd</sup> mate
P6	GND	
P7	5V Precharge	5V Power
P8	5V Precharge	5V Power
P9	5V Precharge	
P10	GND	
P11	Reserved	
P12	GND	1 <sup>st</sup> mate
P13	Not Used (12V Precharge)	N/A
P14	Not Used (12V)	
P15	Not Used (12V)	

**Signal Segment**

PIN	Signal Name	Description
S1	GND	
S2	RxP	Differential Signal pair for Receive
S3	RxN	
S4	GND	
S5	TxN	Differential Signal pair for Transmit
S6	TxP	
S7	GND	

**Revision History**

July 30, 2010 Rev-A Preliminary Product Specification Released

■ ■ **UltraDrive MX2 Series**

**SATA Solid State Drive**

**Mechanical Specifications**

