

■ DuraDrive AX

**SATA Solid State Drive**



The DuraDrive AX offers enhanced durability, reliability, and performance in non-standard environments that require sturdy devices. With the ability to withstand extreme shocks, humidity, altitude, and temperatures, the AX is ideal for applications such as aerospace, the medical industry, embedded and industrial systems. With ECC/EDC support, bad bit management firmware, and patented wear leveling technology, the DuraDrive AX offers reliability when it comes to your data.

**Features**

- SATA III Interface
- Max Speed: Read up to 530 MB/s, Write up to 210MB/s
- Capacities up to 256GB

**Specifications**

<b>Capacity</b>	64GB – 256GB
<b>Interface</b>	SATA III
<b>Form Factor</b>	1.8"
<b>Dimensions</b>	69.85 x 50.0 x 9.0 mm
<b>Power Supply</b>	5V +/- 10%
<b>Performance(MB/sec)</b>	530/210

**Environmental Specifications**

<b>Humidity</b>	5% to 98%
<b>Operating Shock</b>	1500G ( duration : 5ms )
<b>Operating Vibration</b>	16G ( 7Hz~2KHz )
<b>Operating Temperature</b>	-40°C to 85°C (I-temp)
	0°C to 70°C (C-temp)

**Ordering Information:**

Industrial Mode (-40°C to 85°C)

Capacity	Industrial Temp
64GB	FTM064101N
128GB	FTM128101N
256GB	FTM256101N

\*EOL Part Number : FTM\*\*\*MU1M

Commercial Mode (0°C to 70°C)

Capacity	Commercial Temp
64GB	FTM064101L
128GB	FTM128101L
256GB	FTM256101L

\*EOL Part Number : FTM\*\*\*MU1L