

■ DuraDrive ET3

IDE/PATA Solid State Drive



Super Talent's DuraDrive ET3 displays the next generation of industrial data storage solutions through enhanced durability, reliability and performance environments considered "too harsh" for a standard drive.

Supporting access times of 0.1ms, the DuraDrive can reach read and writes speeds of up to 90/100 MB/sec. With ECC/EDC support, bad bit management firmware and patented wear leveling technology, the DuraDrive ET3 is sure to fit your computing needs.

Featuring the industry standard 2.5" form factor and IDE/PATA interface, the DuraDrive ET3 is 100% interchangeable with conventional 2.5" IDE/PATA hard drives.

This SSD is geared specifically for applications that require high shock, vibration, and/or reliability. Examples include:

- Medical Industry
- Embedded/Industrial Systems
- Enterprise Computing
- Aerospace
- Casino Gaming

Physical Specifications

	DuraDrive ET3
Form Factor	2.5"
Capacity	32-512GB(MLC), 32-256GB(SLC)
Dimensions	100.2 x 69.85 x 9.5 mm
Interface	IDE/PATA
NAND Flash	MLC/SLC
Power Supply	5V ± 10%
Package	Complete metal housing

Environmental Specifications

Shock (Operating)	1500G
Vibration (Operating)	20G
Operating Temperature (Industrial)	-40°C ~ 85°C
Operating Temperature (Commercial)	0°C ~ 70°C

Ordering information

MLC	
32 GB	FE8032102D
64 GB	FE8064102D
128 GB	FE8128102D
256 GB	FE8256102D
512GB	FE8512102D

SLC	
32 GB	FEK032102D
64 GB	FEK064102D
128 GB	FEK128102D
256GB	FEK256102D